

## F 82

## FORWARD VIBRATORY PLATE





- Devibrated and ergonomic handle with low hand-arm-vibration levels.
- The F 82 can cope with the toughest of jobs since parts of the engine and transmission are protected by a cover.
- The chassis and handlebar are galvanized providing a superior corrosion protection and maintenance-free life.
- The excentric element has permanently lubricated bearings that are maintenance free.
- The handlebar can easily be removed without any tools, for instance, during transportation.

## For compaction of sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable, which imply low maintenance costs.

• The Swepac F 82 is the ideal high performance all-round machine.

TECHNICAL DATA – <b>Swepac f 82</b>		
Weight, net	82 kg	
Base plate, width x length	430 x 610 mm	
Height, max / min	990 / 980 mm	
Length, max / min	1070 / 640 mm	
Engine	Honda GX 160	
Fuel tank capacity	3.1 liter	
Fuel	Unleaded or alkylate petrol	
Engine output, max	3.6 kW (4.8 hp)	
Centrifugal force	15 kN	
Frequency	93 Hz	
Working speed	0-25 m/min	

Hand/arm vibrations HAV according to ISO 5349 on gravel surface	3.2 m/s <sup>2</sup>
Guaranteed sound-power level, LWA	105 dB(A)
Sound pressure level (at operator's ear), OP	90 dB(A)

## PART NUMBER

305740-02 F 82 with Honda petrol engine and devibrated handle

ACCESSORIES	
305705	Transport wheels for F 82
305322	Vulkollan plate with brackets

ш

2021-05\_GB