Dynapac CC800

Double drum vibratory rollers





Technical data

Masses Masses	
Max. operating mass	1665 kg
Operating mass (incl. ROPS)	1575 kg
Module mass (front/rear)	740 kg/835 kg

Compaction		
Centrifugal for	orce	17 kN
Nominal amp	olitude	0.4 mm
Static linear	oad (front/rear)	9.3/10.4 kg/cm
Vibration free	quency	70 Hz
Water tank		110

Hydraulic system	
Driving	Axial piston pump with variable displacement and servo. 2 radial piston motors with constant displacement.
Vibration	Gear pump/motors with constant displacement.
Steering	Gear pump with constant displacement.
Service brake	Hydrostatic in forward and reverse lever.
Parking/ Emergency brake	Failsafe brake in both drums.

Engine	
Manufacturer/Model	Kubota D1105-E4B T4f
Туре	Water cooled diesel
Rated power, SAE J1995	18 kW (24 hp) @ 2800 rpm
Fuel tank capacity	23 I


Traction	
Speed range	0 -9 km/h
Vertical oscillation	±13°
Theor. gradeability	40 %

Dynapac CC800

Double drum vibratory rollers



Technical data



Dimensions	
A. Wheelbase	1350 mm
B. Width	870 mm
C. Curb clerance	455 mm
D. Drum diameter	588 mm
H1. Height, with ROPS/cab	2300 mm
H2. Height, w/o ROPS/cab	1585 mm
K. Ground clearance	250 mm
L1. Length	2040 mm
L2. Length (ROPS)	2095 mm
O1. Overhang, right	35 mm
O2. Overhang, left	35 mm
R1. Turning radius, outside	2650 mm
S. Drum shell thickness	14 mm
W. Drum width	800 mm
α. Steering angle	±34°

